














IS-MP.1

The IS-MP.1 is a handheld reader for easy and efficient reading of RFID/NFC TAGs that are located closely together or positioned in areas that are difficult to access. The TAG information can be viewed directly on the OLED display, transferred via Bluetooth or read from the storage via USB.

TECHNICAL FEATURES

 <p>ATEX approval: EX-zone 1/21 Ⓜ II 2G Ex ib IIC T4 Gb Ⓜ II 2D Ex ib IIIC T135°C Db IP6X</p>	 <p>IECEx approval: EX-zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X</p>	 <p>vibration feedback</p>	 <p>size: 190 x 30 x 35 mm, weight: 130 g</p>
 <p>battery capacity for 2.000 Bluetooth readings</p>	 <p>memory for 1000 readings</p>	 <p>Bluetooth® 4.0 LE</p>	 <p>OLED-display</p>
 <p>1 ... 3 cm reading distance</p>	 <p>RFID/NFC tag-reader*: LF 125kHz, LF 134,2 kHz  FDX-B + HDX, HF and NFC 13,56 MHz, UHF 868 MHz</p>		

FURTHER FEATURES

 <p>IP64 certified</p>	 <p>operation range from -20 °C to 60 °C</p>	 <p>real-time clock</p>	 <p>apps with remote use available</p>
---	---	--	---

* = Allows individual configuration.

CONTENTS

IS-MP.1, USB cable i.safe PROTECTOR, quick start manual and safety instructions

➤ Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. ➤ i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. ➤ © 2017 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | DW3170216